





W = Width, H = Height, D = Depth

230V∼ 50Hz ⊕ ∆ (€ <u>×</u>



## Item number

DEFA no: 450020 Weight: 260 gr. Packing: 8 pack.

## Part of

Available as single unit, in the Chargerkit 1204, Charger/ComfortKit 1350 and 1850. It's also available in some DEFA WarmUp kits together with SmartStart ™ and Termini™.

## **Use & Mounting**

MultiCharger 1204 can be used to charge all open or closed types of 12V lead/acid inclusive AGM and GEL batteries. Fit and install the charger according to the enclosed usage & installation guide.

www.defa.com

## **DEFA MultiCharger 1204**

DEFA MultiCharger 1204 is design to be mounted in an vehicles engine compartment room. It's easy to fit and secure your battery to always be fully charged. Features:

- Advanced switch-mode charging electronics, which help to preserve the battery. Therefore, the charger can be permanently connected.
- The temperature-compensated charging voltage ensures that the battery will be fully charged in all conditions
- LED indicator showing the 4 step charging modes (S1, S2, S3 og S4).
- If the battery is so heavily loaded during the trickle charging process that the battery voltage drops to below 13V, the charger automatically switches to full-power mode (boost mode).

DEFA AS is conforming to the requirements of both ISO 9001-2008, ISO 14001:2004 and OHSAS 18001:2007. In addition to this, our engine heaters and cables are conforming to the requirements of ISO/TS 16949:2002.

Technical specifications (@ +20°C)	
230V 50-60Hz	
65	
4	
-40/+85	
14,3	
13,3 - 13,8	
1,0	
85	
IP 65	
84/103/42	
260	
7,5	
1,0	
EN 60335-1:2002, EN 60335-2-29:2004.	
EN 55014-1:2006, EN 55014-2:1997;A1, EN 61000-3-2:2006, EN 61000-3-3:1995;A1;A2	
EN 50366:2003;A1	

<sup>\*</sup> When not connected to 230V.

